

PaperOne™ Laser

Product Information and Specifications

PAPERONE™ LASER is engineered for converting needs. PAPERONE™ LASER is available in high-bright white shade and is produced using 100% ECF pulp from PEFC certified renewable plantation fibre. This paper is alkaline sized to meet ISO 9706 for archival quality.

Benefits



No Post Print Curling



Vibrant Colour



Sharp & Crisp Lines



Lesser Colour Bleed

Properties	Unit	Testing Method	Tolerance	65	67	70	75	80
Grammage	gsm	ISO 536	± 4%	65	67	70	75	80
Thickness	µm	ISO 534	± 3	88	90	97	103	107
CIE Whiteness		ISO 11475	± 2	158	158	158	158	158
ISO Brightness	%	ISO 2470	± 2	94	94	94	94	94
ISO Opacity	%	ISO 2471	± 2	90	91	94	94	95

Applications

- Statements
- Plotter Rolls
- Continuous Forms
- Trans-promotional
- Letterheads
- Variable Data Books and Magazines

Finishings

- Gluing
- Spiral Binding
- Limp Binding
- Saddle Stitch
- Perfect Binding
- Cutting and Folding

Printing Methods

- Laser
- Xerographic



Specification are accurate as of April 2026 in accordance with international standards for tolerances and subjected to changes. Based on benchmarking studies under controlled conditions, subject to change. The values are as testing results in Riau Paper Laboratory, which has been applying TAPPI T402 as room condition standard in 23 ± 1 °C and 50 ± 2% humidity